

Service Manual



MELROE
INGERSOLL-RAND

6720326(8-90)

Printed in U.S.A.

© Melroe Company 1990




MAINTENANCE SAFETY

! WARNING


Instructions are necessary before operating or servicing machine. Read and understand the Operation & Maintenance Manual, Handbook and signs (decals) on machine. Follow warnings and instructions in the manuals when making repairs, adjustments or servicing. Check for correct function after adjustments, repairs or service. Untrained operators and failure to follow instructions can cause injury or death.

W-2003-0199


! Safety Alert Symbol: This symbol with a warning statement, means: "Warning, be alert! Your safety is involved!" Carefully read the message that follows.




! Never service the Bobcat® Skid Steer Loader without instructions.




! Use the correct procedure to lift or lower operator's seat.




! Cleaning and maintenance are required daily.




! Have good ventilation when welding or grinding painted parts.
! Wear dust mask when grinding painted parts. Toxic dust and gas can be produced.
! Avoid exhaust fumes. Fumes which can kill without warning. Exhaust system must be properly sealed.




! Disconnecting or loosening any hydraulic tubeline, hose, fitting, component or a part failure can cause lift arms to drop. Do not go under lift arms when raised unless supported by an approved lift arm support device. Replace if damaged.



! Never work on loader with lift arms up unless lift arms are held by an approved lift arm support device. Replace if damaged.
! Never modify equipment or add attachments not approved by Bobcat Company.



! Stop, cool and clean engine of flammable materials before checking fluids.
! Never service or adjust loader with the engine running unless instructed to do so in the manual.
! Avoid contact with leaking hydraulic fluid or diesel fuel under pressure. It can penetrate the skin or eyes.
! Never fill fuel tank with engine running, while smoking or when near open flame.



! Keep body, jewelry and clothing away from moving parts, electrical contacts, hot parts and exhaust.
! Wear eye protection to guard from battery acid, compressed springs, fluids under pressure and flying debris when engines are running or tools are used. Use eye protection approved for type of welding.
! Keep rear door closed except for service. Close and latch door before operating the loader.



! Lead-acid batteries produce flammable and explosive gases.
! Keep arcs, sparks, flames and lighted tobacco away from batteries.
! Batteries contain acid which burns eyes or skin on contact. Wear protective clothing. If acid contacts body, flush well with water. For eye contact flush well and get immediate medical attention.

Maintenance procedures which are given in the Operation & Maintenance Manual can be performed by the owner/operator without any specific technical training. Maintenance procedures which are **not** in the Operation & Maintenance Manual must be performed **ONLY BY QUALIFIED BOBCAT SERVICE PERSONNEL**. Always use genuine Bobcat replacement parts. The Service Safety Training Course is available from your Bobcat dealer.

MSW01-0600




Bobcat®

FOREWORD

This manual is for the Bobcat loader mechanic. It provides necessary servicing and adjustment procedures for the Bobcat loader and its component parts and systems. Refer to the Operation & Maintenance Manual for operating instructions, starting procedure, daily checks, etc.

A general inspection of the following items must be made after the loader has had service or repair.


1. Check that the ROPS/FOPS (Including sidescreens) is in good condition and is not modified.




9. Enclosure door latches must open and close freely.




2. Check that ROPS mounting hardware is tightened and is Melroe approved.




10. Bob-Tach wedges and linkages must function correctly and be in good condition.




3. The seat belt must be correctly installed, functional and in good condition.




11. Safety treads must in good condition.




4. The seat bar and pedal interlocks must be correctly adjusted, clean and lubricated.



12. Check for correct function of indicator lamps (Optional on some models).




5. Machine signs must be legible and in the correct location.



13. Check hydraulic fluid level, engine oil level and fuel supply.



6. Steering levers and foot pedals must return to neutral.



14. Inspect for fuel, oil or hydraulic fluid leaks.




7. Check for correct function of the work lights and travel lights.




15. Lubricate the loader.




8. The parking brake must function correctly.




16. Check the condition of the battery and cables.




17. Inspect the air cleaner for damage or leaks. Check the condition of the element.




18. Check the electrical charging system.




19. Check tires for wear and pressure.




20. Inspect for loose or broken parts or connections.




21. Operate the loader and check all functions.



22. Check for any field modification not complete.



Recommend to the owner that all necessary corrections be made before the machine is returned to service.



[Buy now](#)

[Bobcat 753 Skid Steer Loader Service Manual PDF](#)

[With Instant Download](#)