

Service Manual

JZ 70

Fru nachine no.834000

PUBLISHED BY THE
TECHNICAL PUBLICATIONS DEPARTMENT
OF JCB SERVICE: ©
CHEADLE ROAD, UTTOXETER
STAFFORDSHIRE, ST14 7BS,
ENGLAND
Tel. (01889) 590312
PRINTED IN ENGLAND

Publication No. 9803/6030

General Informa	ation 1
Care & Safety	2
Routine Mainte	nance 3
Att: coments	A
Body & Framew	vork B
Electrics	C
Controls	D
Hydraulics	Ε
Transmission	F
Brakes	G
Engine	K

Introduction

This publication is designed for the benefit of JCB Distributor Service Engineers who are receiving, or have received, training by JCB Technical Training Department.

These personnel should have a sound knowledge of workshop practice, safety procedures, and general techniques associated with the maintenance and repair of hydraulic earthmoving equipment.

Renewal of oil seals, gaskets, etc., and any component showing obvious signs of wear or damage is expected as a matter of course. It is expected that components will be cleaned and lubricated where appropriate, and that any opened hose or pipe connections will be blanked to prevent excessive loss of hydraulic fluid and ingress of dirt. Finally, please remember above all else **SAFETY MUST COME FIRST!**

The manual is compiled in sections, the first three are numbered and contain information as follows:

- 1 = General Information includes torque settings and servicionals.
- 2 = Care & Safety includes warnings and cautions pertine o a pects of workshop procedures etc.
- 3 = Routine Maintenance includes service schedules at recommended lubricants for the whole machine.

The remaining sections are alphabetically coded and deal with Dismantling, Overhaul etc. of specific components, for example:

- A = Attachments
- B = Body & Framework ...etc

The page numbering in each alphabetically for the insertion of new items in later issues of the manual.

Section contents, technical data, sirc it descriptions, operation descriptions etc. are inserted at the beginning of each alphabetically coded section.

All sections are listed on the foot cover; tabbed divider cards align directly with individual sections on the front cover for rapid reference.

Where a torque setting is given as a single figure it may be varied by plus or minus 3%. Torque figures indicated are for dry threads, hence for ubric ted threads may be reduced by one third.

'Left Hand' and 'Right Hand' are as viewed from the rear of the machine facing forwards.

Note: In bis ranual the term 'swing' may sometimes be used in place of 'slew' and the term 'arm' may sometimes be used in place of 'Grever'.

9803/6030 Issue 1

i

Contents	Page No.
Bolt and Nut Torque Specifications	1 - 1
General Torque Settings	1 - 2
Service Tools Section B - Body and Framework Section C - Electrics Section E - Hydraulics	3 - 1 4 - 1 5 - 1
Sealing and Retaining Compounds	9 - 1



9803/6030 Issue 1

Buy now

JCB Excavators JZ70 Service Manual PDF

With Instant Download